



Technical Specifications

Items	Diamond Pro Lite
Thickness (coating+TPU+adhesive)	6.3mil
TPU Source	Merquisa(Spain)
Elongation at break	>_300%
Glossiness	92.80
Yellowing Test	AE< 1/1000hours
Hydrophobic Property	R9-R10
Removal Test	No damage to the original car paint and no glue left when removing from the car
Warranty	4 years
TPU Thickness	5mil
Self-healing coating	15um
Adhesive Layer	25um
Tensile Strength	28Mpa (4000psi)
Stain Resistance(normal temperature)	Can be removed by tissue
Again Test	No significant change
Acid Resistance	No adnormalities
Rain Spot	No adnormalities
Size	1.52M (60'') * 15M (50')

Warranty

Diamond Pro Paint Protection Film Warranty

Estoril extensive warranty certifies all Diamond Pro product lines to be free of any manufacturing and workmanship defects for a period of four (4) years from the date of installation on painted automotive surfaces.

This warranty covers only those defects which can be attributed to the manufacturing process of the film such as fading, color change, cracking, bubbling or delamination.

Defects or accidents caused by inappropriate installation processes or facilities, intentional misuse, exceptional damage due to large debris, collision or vandalism, among others, are considered part of the product's regular wear and tear and are excluded from this warranty.

Please register your product, by completing the form below, to facilitate a quick and efficient process in the event of a warranty claim. Replacement of the defective film is the only form of compensation offered by this warranty and will be provided exclusively upon display of a valid proof of purchase issued by an authorized dealership. All claims should be addressed in first instance to the original dealership or installer, only in cases where such a claim proves unsatisfactory will Estoril provide manufacturer coverage.

This warranty does not cover Diamond Pro products installed on vehicles used for commercial or professional activities, including but not limited to racing cars, courier fleets and rentals.

Features

Heat Activated Self-Healing Topcoat
Constructed from an elastomeric polyurethane, Diamond Pro will self-heal light scratches & swirl marks with a light heat application to the films surface.

Non-Yellowing

Our proprietary film formulation will not yellow from UV exposure, ensuring protected areas are nearly invisible.

Discoloration & Stain Resistant

Dont worry about specs, spots, or splotches from contaminants. Diamond Pro is stain resistant & will maintain clarity under the harshest conditions.

Prevents Wear & Tear

Stop rock chips, nicks & scratches in the paint, and keep your vehicle looking as good as the day it rolled off the lot.

Edge Seal Technology

Lifting & delamination are a thing of the past. Our signature Edge Seal Technology ensures film stays stuck & keeps surfaces protected from contaminants.

